Certificate of Analysis

Polymer type: Poly(styrene) without initiator end group
Part No: PSS-psoi60k
Lot No: ps5033oi

Molar Mass Distribution



GPC/SEC - Conditions

Sample concentration	1,00 g/l	Inject volume	20 µl
Solvent	THF	Flow rate	1,00 ml/min
Precolumn [8 x 50 mm]	PSS SDV 5µm	Temperature	23,0° C
Columns [analytical, each 8 x 300 mm]	PSS SDV 5µm 10e3Å / 10e5Å / 10e6Å		
Data Acquisition Software	PSS WinGPC	Operator	S. Fugmann

GPC/SEC - Results

Detector	Mw [Da]	Mn [Da]	Mp [Da]	PDI [Mw/Mn]
Shodex RI 71	59600	57300	58200	1,04

Note:
Mw = Weight Average Molecular Weight
Mn = Number Average Molecular Weight
Mp = Molar Mass at the Peak Maximum
PDI = Polydispersity Index

Storage: Store the tightly recapped polymer standard in a dry, dark, cool area; e.g. a refrigerator (4 °C).
Date of expiry: See product label.

Manufacture and control according to PSS method of analysis

Dr. T. Hofe
production director

PSS Polymer Standards Service GmbH
In der Dalheimer Wiese 5
55120 Mainz | Germany
Phone +49 6131 96239-0
Fax +49 6131 96239-11
E-Mail info@pss-polymer.com
Web www.pss-polymer.com

Polymer Standards Service-USA, Inc.
160 Old Farm Rd, Suite A
Amherst | MA 01002 | USA
Phone +1 413 835-0265
Fax +1 413 835-0354
E-Mail usa@pss-polymer.com
Web www.pss-polymer.com

TÜVRheinland CERT ISO 9001